

Claims

- [c1]A weld wire comprising:
a sheath encapsulating a metal core made of powdered metal, wherein a fill
percentage of the metal core is higher than approximately 12%; and
the metal core having a core composition alloyed with an alloying element or an
combination of elements comprising Cr, Mo, V, W, Hf and Nb or combinations
thereof, wherein a total weight percentage of the alloying element or the
combination of elements in the core composition does not exceed
approximately 1%.
- [c2]2.The weld wire of Claim 1, wherein the alloying element is Mo in the amounts
selected from the range of about 0 to about 0.5 percent by weight.
- [c3]3.The weld wire of Claim 1, wherein the fill percentage of the metal core is
selected from the range of about 12% to about 30 %.
- [c4]4.The weld wire of Claim 1, wherein the total percentage of the combination of
elements is selected from the range of about 0.4% to about 0.8%.
- [c5]5.The weld wire of Claim 1, wherein the composition mainly comprises,
approximately,

C 0.021–0.043%,
Mn 1.0–1.69.0%,
Si 0.33–0.66%, and
Ni 0.016–0.033%

and the fill percentage of the metal core is higher than approximately 12%.
- [c6]6.The weld wire of Claim 1, wherein the alloying combination comprises,
approximately,
Cr Up to 0.5
Mo Up to 0.5
W Up to 0.5
V Up to 0.5

Hf Up to 0.5
Nb Up to 0.5.

- [c7] 7. An improved productivity weld wire comprising a sheath encapsulating a steel core having a core fill percent of more than 12%; and the steel core having a composition comprising an alloying element selected from the group consisting of Cr, Mo, V, W, Hf and Nb and combinations thereof, wherein a deposition rate of the weld wire when used during welding increases with the increase of the core fill percent.
- [c8] 8. The improved productivity weld wire of Claim 7, wherein the deposition rate increases from about 15 lb/hr for the core fill percent of about 12% to the deposition rate of about 20 lb/h for the core fill percent of about 30%.
- [c9] 9. The improved productivity weld wire of Claim 7, wherein a total weight percentage of an alloying element does not exceed approximately 1%.
- [c10] 10. The improved productivity weld wire of Claim 8, wherein a total weight percentage of Mo varies from about 0% to about 0.4%.
- [c11] 11. The improved productivity weld wire of Claim 7, wherein the steel core is made of a compacted metal powder.
- [c12] 12. An improved productivity weld wire comprising:
a sheath encapsulating a metal core, wherein a core fill percent of the metal core is higher than 12%; and
the metal core having a composition alloyed with an alloying element or a combination of elements comprising Cr, Mo, V, W, Hf and Nb or combinations thereof, wherein a total weight percentage of the alloying element or the combination of elements in the core composition does not exceed approximately 1%, and wherein a travel speed of the weld wire when used in welding ranges from about 65 in/min to about 145 in/min.
- [c13] 13. The improved productivity weld wire of Claim 12, wherein the travel speed of the wire when used in welding is a maximum travel speed ranging from about

80 in/min to about 145 in/min for the core fill percent ranging from about 12% to about 30 %.

[c14] 14.The improved productivity weld wire of Claim 12, wherein the travel speed of the wire when used in welding increases from about 65 in/min to about 90 in/min.

[c15] 15. The improved productivity weld wire of Claim 13, wherein the maximum travel speed of the wire when used in welding corresponds to the composition comprising a percentage of Mo ranging from about 0% to about 0.4%.

[c16] 16.A method of manufacturing a weld wire comprising:
forming a sheath into a shape which can be filled with a metal powder;
filling the sheath with the metal powder, the metal powder having a composition alloyed with an alloying element or an combination of elements comprising Cr, Mo, V, W, Hf and Nb or combinations thereof, wherein a total weight percentage of the alloying element or the combination of elements in the core composition does not exceed approximately 1%;
compacting the metal powder to form a metal core; and
drawing the wire to achieve a core fill percentage of the metal core no less than 12%.

[c17] 17. The method of Claim 16, wherein the core fill percentage ranges from about 12% to about 30%.

[c18] 18.The method of Claims 17, wherein the alloying element is Mo and wherein the total weight percentage of Mo ranges from about 0% to about 0.4 %.

[c19] 19.The method of Claim 16, wherein the total weight percentage of the combination ranges from about 0.4% to about 0.8%.

[c20] 20.The method of Claim 16, wherein the alloying combination comprises,
approximately,
Cr – Up to 0.5
Mo – Up to 0.5

Nb – Up to 0.5.

1. 1977-1978 2. 1978-1979 3. 1979-1980 4. 1980-1981 5. 1981-1982 6. 1982-1983 7. 1983-1984 8. 1984-1985 9. 1985-1986 10. 1986-1987 11. 1987-1988 12. 1988-1989 13. 1989-1990 14. 1990-1991 15. 1991-1992 16. 1992-1993 17. 1993-1994 18. 1994-1995 19. 1995-1996 20. 1996-1997 21. 1997-1998 22. 1998-1999 23. 1999-2000 24. 2000-2001 25. 2001-2002 26. 2002-2003 27. 2003-2004 28. 2004-2005 29. 2005-2006 30. 2006-2007 31. 2007-2008 32. 2008-2009 33. 2009-2010 34. 2010-2011 35. 2011-2012 36. 2012-2013 37. 2013-2014 38. 2014-2015 39. 2015-2016 40. 2016-2017 41. 2017-2018 42. 2018-2019 43. 2019-2020 44. 2020-2021 45. 2021-2022 46. 2022-2023 47. 2023-2024 48. 2024-2025 49. 2025-2026 50. 2026-2027 51. 2027-2028 52. 2028-2029 53. 2029-2030 54. 2030-2031 55. 2031-2032 56. 2032-2033 57. 2033-2034 58. 2034-2035 59. 2035-2036 60. 2036-2037 61. 2037-2038 62. 2038-2039 63. 2039-2040 64. 2040-2041 65. 2041-2042 66. 2042-2043 67. 2043-2044 68. 2044-2045 69. 2045-2046 70. 2046-2047 71. 2047-2048 72. 2048-2049 73. 2049-2050 74. 2050-2051 75. 2051-2052 76. 2052-2053 77. 2053-2054 78. 2054-2055 79. 2055-2056 80. 2056-2057 81. 2057-2058 82. 2058-2059 83. 2059-2060 84. 2060-2061 85. 2061-2062 86. 2062-2063 87. 2063-2064 88. 2064-2065 89. 2065-2066 90. 2066-2067 91. 2067-2068 92. 2068-2069 93. 2069-2070 94. 2070-2071 95. 2071-2072 96. 2072-2073 97. 2073-2074 98. 2074-2075 99. 2075-2076 100. 2076-2077 101. 2077-2078 102. 2078-2079 103. 2079-2080 104. 2080-2081 105. 2081-2082 106. 2082-2083 107. 2083-2084 108. 2084-2085 109. 2085-2086 110. 2086-2087 111. 2087-2088 112. 2088-2089 113. 2089-2090 114. 2090-2091 115. 2091-2092 116. 2092-2093 117. 2093-2094 118. 2094-2095 119. 2095-2096 120. 2096-2097 121. 2097-2098 122. 2098-2099 123. 2099-2100 124. 2100-2101 125. 2101-2102 126. 2102-2103 127. 2103-2104 128. 2104-2105 129. 2105-2106 130. 2106-2107 131. 2107-2108 132. 2108-2109 133. 2109-2110 134. 2110-2111 135. 2111-2112 136. 2112-2113 137. 2113-2114 138. 2114-2115 139. 2115-2116 140. 2116-2117 141. 2117-2118 142. 2118-2119 143. 2119-2120 144. 2120-2121 145. 2121-2122 146. 2122-2123 147. 2123-2124 148. 2124-2125 149. 2125-2126 150. 2126-2127 151. 2127-2128 152. 2128-2129 153. 2129-2130 154. 2130-2131 155. 2131-2132 156. 2132-2133 157. 2133-2134 158. 2134-2135 159. 2135-2136 160. 2136-2137 161. 2137-2138 162. 2138-2139 163. 2139-2140 164. 2140-2141 165. 2141-2142 166. 2142-2143 167. 2143-2144 168. 2144-2145 169. 2145-2146 170. 2146-2147 171. 2147-2148 172. 2148-2149 173. 2149-2150 174. 2150-2151 175. 2151-2152 176. 2152-2153 177. 2153-2154 178. 2154-2155 179. 2155-2156 180. 2156-2157 181. 2157-2158 182. 2158-2159 183. 2159-2160 184. 2160-2161 185. 2161-2162 186. 2162-2163 187. 2163-2164 188. 2164-2165 189. 2165-2166 190. 2166-2167 191. 2167-2168 192. 2168-2169 193. 2169-2170 194. 2170-2171 195. 2171-2172 196. 2172-2173 197. 2173-2174 198. 2174-2175 199. 2175-2176 200. 2176-2177 201. 2177-2178 202. 2178-2179 203. 2179-2180 204. 2180-2181 205. 2181-2182 206. 2182-2183 207. 2183-2184 208. 2184-2185 209. 2185-2186 210. 2186-2187 211. 2187-2188 212. 2188-2189 213. 2189-2190 214. 2190-2191 215. 2191-2192 216. 2192-2193 217. 2193-2194 218. 2194-2195 219. 2195-2196 220. 2196-2197 221.	
--	--